

517,440

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 December 2003 (18.12.2003)

PCT

(10) International Publication Number
WO 03/104785 A1

(51) International Patent Classification⁷: **G01N 27/07**,
33/04, G01R 27/22, A01J 5/013

(21) International Application Number: PCT/NZ03/00104

(22) International Filing Date: 26 May 2003 (26.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 10 June 2002 (10.06.2002) NZ
10 DEC 02

(71) Applicant (for all designated States except US): **RADIAN TECHNOLOGY LIMITED** [NZ/NZ]; 1 Coolidge Street, Brooklyn, Wellington (NZ).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NILSON, Ross,**

Richard [NZ/NZ]; 1 Coolidge Street, Brooklyn, Wellington (NZ). **THOMSON, Graeme, Alexander** [NZ/NZ]; 28 Thane Road, Roseneath, Wellington (NZ). **FORREST, Campbell, Ernest** [NZ/NZ]; 2/104 Ellice Street, Mt Victoria, Wellington (NZ). **SMITH, Jeremy, Bruce** [NZ/NZ]; 2/104 Ellice Street, Mt victoria, Wellington (NZ).


(74) Agent: **BALDWIN SHELSTON WATERS**; P.O. Box 852, Wellington (NZ).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: MEASUREMENT AND MONITORING SYSTEM OF DAIRY STOCK AND PLANT



(57) Abstract. A measurement sensor where a mixed solution enters a manifold (1) and is separated in an entry chamber (2) by a whirlpool and/or setting effect. An accumulation chamber (3) and outflow (4) positioned in the lower peripheral of the entry chamber (2) causes the separated solution to preferentially flow to a sensing tube (6) with surface to sectional area dimensions optimised for high frequency electric field measurement of solution parameters used to determine capacitance and conductivity. Overflow of mixed solution enters (5) similar sensing tubes (7), for mixed flow measurements used to determine mass and flow rate. The number and size of the overflow tubes (7) give minimal head loss through the manifold. Solution is recombined in an exit chamber (10) that causes fluid dynamic restrictions (8) to extend solution residence time in measurement tube (6) before exiting the manifold (11). Also disclosed is measurement of a fluid parameter by improving the measurement sensitivity by at least partially canceling the effect of dielectric properties of the containment wall through which the parameter is sensed, and a method for determining plant performance using stored performance profiles.

WO 03/104785 A1